

North America's #1 Brand of High-Pressure Cleaning Equipment

# MODEL 5555555 Hot-Water Pressure Washer

## **Electric / Direct Drive**




*Heater coils* carry a 5-year warranty

Simple, easy-to-use control panel includes adjustable

duty heater and pump motor

switches

temperature control plus heavy-



**Stainless-steel coil skin** provides extra durability to withstand the elements **Built-in wand and hose holder** provides convenient storage

Heavy-duty trigger gun

and wand with insulated

50-ft. length of highpressure hose for easy

large cleaning area

maneuverability around a

**Pressure relief valve** protects the machine and user from thermal expansion

cool grips

**Convenient hose-reel bracket** accepts swivel or stationary reels for ease in hose maneuverability and storage (extra bracket needed for stationary reels)

2 HP, 115V, 1PH electric motor is drip proof and comes with thermal overload protection and manual reset

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning

**36-ft. power cord** with safety **Ground Fault Circuit Interrupter** (GFCI breaker)

Rust-proof, noncontaminating polyethylene fuel tank includes fuel gauge in cap

Solid flat free tires

FEATURES

- 2.2 GPM @ 1300 PSI / Direct-Drive Pump
- Oil-Fired Heater
- 7-Yr Pump Warranty

ETL-Certified to UL-1776 safety standards



Hotsy duplex, direct-drive, positive-displacement pump carries a seven-year warranty on the crankcase and features NESTechnology with U-Seals for longer life.

Adjustable, spray-angle nozzle with 0° to 80° spray patterns adjusts easily under high pressure

www.Hotsy.com

■ Oil-Fired Heater ■ 2.2 GPM @ 1300 PSI ■ Hotsy Duplex Pump with 7-yr warranty ■ Portability standard ■ ETL-Certified for safety

# **Designed for tough, industrial cleaning.**

SPECIFICATIONS												DIRECT DRIVE	
MODEL	GPM	PSI	HP	VOLT/PH	AMP	FUEL	BTU/HR	PUMP	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)	
555SS	2.2	1300	2	115/1	20	Oil	214,300	Duplex-HHC165L.1	Direct	Std	50'	360	

Dimensions: 33"l x 27"w x 41.5"h

#### DON'T FORGET THE SOAP!

Hotsy pressure washers clean best when matched with specially formulated Hotsy detergents. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. All are highly



concentrated, so a little goes a long way.

HOTSY SOLUTION SELECTOR What's the best detergent for your next job? Find out with our solution selector. Scan this QR code or visit HOTSY.com

#### **SERVICE & REPAIR**

Hotsy has more than 175 local dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Hotsy has factory-trained service technicians who will provide on-site maintenance for your cleaning equipment. Our techs have most common replacement parts on their service truck, and will quickly have your washer running smoothly.

FIND OUT MORE ONLINE: HOTSY.COM

### **OPTIONS FOR MODEL 555SS**

- 8" Oil-Fired Draft Dampener
- 360° Pivot Hose Reel Available in 100' and 200'

### **PARTS & ACCESSORIES**

Your local Hotsy dealer would be happy to provide an onsite demonstration to determine which pressure washer accessories will help speed cleaning and lower your costs. Hotsy dealers stock thousands of pressure washer replacement parts such as high pressure hose, trigger guns, high pressure nozzles, pumps, engines, motors, unloaders, filters and wands. In addition, you'll find a number of accessories designed to speed cleaning, the most common accessories are telescoping wands, pivot and non-pivot hose reels, flat surface cleaners and high

pressure turbo nozzles.



Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631 www.Hotsy.com email: info@Hotsy.com P/N 8.914-213.0 Effective 2/16

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified. A member of KÄRCHER North America ©2016 Hotsy

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at  $\pm$  10% and in some cases are tighter within ±5% of listed specifications.