5700/5800 SERIES

FEATURES

8.0 to 9.5 GPM @ 2500 to 3000 PSI Stainless Steel Coil Skin 20 HP



Upright, vertical coil delivers high efficiency and maintains constant temperature using oil, natural gas or liquid propane.

Controls for the pump, burner and detergent are easily accessible.

Remote ready for operation in wash bays.

PRESSURE WASHERS / SINCE 1970

HOT WATER

ELECTRIC

BELT DRIVE

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning.

Stainless steel coil skin provides extra durability to withstand overspray.

Elevated gas valve protects valve from water damage, and is located at the back corner for easy installation and service.

Burner assembly pivots down to allow access to burner ring and pilot assembly for maintenance.

Insulated Hotsy trigger gun and insulated wand with ergonomic, adjustable side handle.

Pressure relief valve protects the machine and user from thermal expansion.

Control panel provides access to the main controls. Remove the front panel to access the Smart Relay for secured control of desired operating settings, such as auto start/stop functionality.

Sleek side and front panels are easily removed for routine maintenance and service access.

50-ft. length of high-pressure hose for easy maneuverability around a large working area.

With its 20 HP motor driving the incomparable Hotsy Triplex Pump and a vertical banded belt, the 5700 and 5800 Series delivers cleaning power up to 9.5 GPM and 3000 PSI.

Quick disconnect stainless steel nozzles are color coded for quick changing between 0°, 15°, 40° spray nozzles.

.....



Motor is mounted to slide out rails for easy removal.

Programmable Smart Control Automation provides complete control over the machine's run time, auto start/stop and time delay shut down functionality.

......



Large frame Hotsy beltdrive pump features NESTechnology with U-Seals for 3 times longer pump life.



OPTIONS FOR 5700/5800 SERIES

12" Power Dampener

Remote Station (1)

R-Con Wireless Remote Kit (2)

Wall Mount Remote Kite (3)

LP Conversion Kit

12" Natural Gas- or LP Gas-Fired Draft Diverter

Soap Solenoid and Switch

Water Inlet Solenoid









5700/5800 SERIES

POWERFUL MODELS FOR TOUGH INDUSTRIAL CLEANING..

Hot-Water **ELECTRIC** Models

Oil, NG or LP-Fired8 to 9.5 GPM @ 2500 to 3000 PSI20 HP

MODEL	PART NO.	GPM	PSI	НР	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	HOSE (FT)	DIMENSIONS (LXWXH)	SHIP WT (LBS)
5730SS	1.109-658.0	8.0	3000	20	230/3	44	0il*	768,000	HX9536L.2	50	51"x31"x63.4"	1,471
5732\$\$-208	1.109-654.0	8.0	3000	20	208/3	55	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5732\$\$	1.109-655.0	8.0	3000	20	230/3	42	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5733SS	1.109-659.0	8.0	3000	20	460/3	23	Oil*	768,000	HX9536L.2	50	51"x31"x63.4"	1,471
5735SS	1.109-656.0	8.0	3000	20	460/3	21	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5736SS	1.109-657.0	8.0	3000	20	575/3	16	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5832\$\$	1.109-651.0	9.5	2500	20	230/3	42	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,471
5832\$\$-208	1.109-650.0	9.5	2500	20	208/3	48	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,471
5835SS	1.109-652.0	9.5	2500	20	460/3	21	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,461
5836SS	1.109-653.0	9.5	2500	20	575/3	16	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,471

^{*}Oil-fired models are not supplied with a fuel tank

DETERGENTS



To clean like a pro, you need to include detergents. Hotsy offers a full line of detergents for cleaning grease, dirt, road grime, aluminum, sanitation and so much more. Our detergents help you clean faster and save money.

PARTS & ACCESSORIES



Clean faster and more efficiently with pressure washer accessories like flat surface cleaners and turbo nozzles.

SERVICE



Hotsy factory-trained technicians keep your equipment running with on-site or in shop maintenance and tuneups. Plus, we repair all brands.

The Pressure Washer The Pros Use. **EST. 1970**

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_10% and in some cases are tighter within +_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

HOTSY.COM

Tel: 800.525.1976 Fax: 888.880.9631 Email: info@hotsy.com

VISIT US ONLINE

Facebook/Instagram HotsyCleaningSystems
LinkedIn Hotsy-Corp
Twitter TheHotsyMan
YouTube HotsyCleaningSystems

© 2023 Kärcher North America P/N HOT_1800 Effective 07/23

Get Hotsy Email Bit.ly/GetHotsy

Distributed by: