



HSS & HSDS SUPERSKID SERIES



PRESSURE WASHERS / SINCE 1970

FEATURES

- 5.0 to 9.5 GPM @ 2500 to 3500 PSI
- Stainless Steel
- Coil Wrap
- Electric Start



HOT WATER

DIESEL

BELT DRIVE

High efficiency **Wayne 12VDC Burner** with proprietary controller

Ready plumbed for connection to remote water tank

50-ft. of two-wire, heavy-duty abrasion resistant **hose**

High flow VRT100 unloader handles 27 GPM @ 5075 PSI

Heavy-duty trigger gun and wand with insulated cool grips

Water resistant control panel includes adjustable temperature control, heavy-duty heater switch, hour meter, volt meter, keyed ignition switch, and nozzle storage

Hotsy triplex, tri-banded belt drive, positive-displacement pump carries a 7-year warranty

Optional adjustable **high-pressure detergent kit** (included with the float tank kit)

HSDS models offer super duty **Hawk pump** with lower pump RPMs for long lasting durability

Optional steam combination control

Upright, diesel-fired burner with stainless-steel coil skin is highly efficient and maintains constant hot water using diesel fuel

Removable frame supports for easy service access

3/4-inch schedule 80 heating coil is wrapped with a thick foil backed blanket insulation, carrying a 5-year non prorated warranty

Rugged square tube frame protects machine's vital components

Fuel/water separator prolongs fuel pump life

Tier IV Kubota Diesel engine in 16 or 24 HP operate longer with two diesel crossedlinked HDPE tanks, 25 gallons each

Safety relief valve protects machine and user

Optional large float tank maintains constant pressure and flow while preventing sediment from entering the machine's components



OPTIONS FOR HSS/HSDS SERIES

Dual Gun Kit - includes necessary fittings, extra hose gun and wand

Steam Kit - includes necessary fittings and panel mount control valve

Float Tank Kit - includes float tank, necessary fittings and panel mount detergent metering valve



Pump size comparison:

The HFR and HHP pumps from Leuco used in the Super Duty models dwarf the standard HX.



SUPER SKID HSS SERIES

Hot-Water DIESEL Belt Drive Models

POWERFUL MODELS FOR TOUGH INDUSTRIAL CLEANING.

■ Gas/Diesel-Powered ■ 4.5 to 8.0 GPM @ 3000 to 4000 PSI ■ Electric Start

MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	BURNER	BTU/HR	PUMP MODEL	HOSE	DIMENSIONS (LXWXH)	SHIP WT (Lbs)
HSS-503069E	1.110-604.0	5.0	3000	Kubota Z602-E4B	599	12V DC	465,000	HX5843R.2	50'-3/8"	73"x37"x64"	1305
HSS-653569E	1.110-605.0	6.5	3500	Kubota D1105-E4B	1123	12V DC	565,000	HX8043R.2	50'-3/8"	73"x37"x64"	1710
HSS-803069E	1.110-606.0	8.0	3000	Kubota D1105-E4B	1123	12V DC	635,000	HX9536.2	50'-1/2"	73"x37"x64"	1715
HSS-952569E	1.110-607.0	9.5	2500	Kubota D1105-E4B	1123	12V DC	780,000	HX1036R.2	50'-1/2"	73"x37"x64"	1715

MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	BURNER	BTU/HR	PUMP MODEL	HOSE	DIMENSIONS (LXWXH)	SHIP WT (Lbs)
HSDS-503069E	1.110-616.0	5.0	3000	Kubota Z602-E4B	599	12V DC	465,000	HHP2750R	50'-3/8"	73"x37"x64"	1610
HSDS-653569E	1.110-617.0	6.5	3500	Kubota D1105-E4B	1123	12V DC	565,000	HHP3650R	50'-3/8"	73"x37"x64"	2005
HSDS-803069E	1.110-618.0	8.0	3000	Kubota D1105-E4B	1123	12V DC	635,000	HFR40FR	50'-1/2"	73"x37"x64"	2015
HSDS-952569E	1.110-619.0	9.5	2500	Kubota D1105-E4B	1123	12V DC	780,000	HFR60FR	50'-1/2"	73"x37"x64"	2020


All models are Electric Start. 12V battery required for all models, but not supplied

DETERGENTS



To clean like a pro, you need to include detergents. Hotsy offers a full line of detergents for cleaning grease, dirt, road grime, aluminum, sanitation and so much more. Our detergents help you clean faster and save money.

PARTS & ACCESSORIES



Clean faster and more efficiently with pressure washer accessories like flat surface cleaners and turbo nozzles.

SERVICE



Hotsy factory-trained technicians keep your equipment running with on-site or in shop maintenance and tune-ups. Plus, we repair all brands.



The Pressure Washer The Pros Use.
EST. 1970

HOTSY.COM

Tel: 800.525.1976

Fax: 888.880.9631

Email: info@hotsy.com

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_10% and in some cases are tighter within +_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

VISIT US ONLINE

Facebook/Instagram HotsyCleaningSystems

LinkedIn Hotsy-Corp

Twitter TheHotsyMan

YouTube HotsyCleaningSystems

Get Hotsy Email Bit.ly/GetHotsy

© 2021 Kärcher North America

P/N HOT_HSS Effective 06/21

Distributed by:



1210 N Oregon Ave, Pasco, WA 99301
northstarhotsy.com | info@northstarhotsy.com
(509) 547-2323